



uEye UI-1550RE colour models, UXGA (1600x1200)

The uEye RE 1550 colour models are equipped with a robust housing which meets in connection with the optional available lens tubes the protection classes IP65 and IP67. The light-sensitive 1/3" sensor with rolling shutter achieves 18 frames per second in fullframe-mode. Binning, Subsampling or AOI offer more than 100 frames.

Included in delivery is the complete uEye software package:

The comfortable, easy to use uEye SDK

Standard drivers like Direct Show (WDM), Active X and TWAIN

Interfaces for popular machine vision software

The extensive uEye Demo and other specific demo-programs, which are all provided also in source code.

- 1/3" CMOS sensor, rolling shutter, progressive scan
- max. 18 fps, 81 fps in AOI-mode with 640x480 pixels
- Exposure: 0,041 ms - 12,8 s (freerun mode)

- Subsampling horizontal and vertical

- AOI horizontal and vertical

- Asynchronous, universal trigger

- Digital out
- Binning horizontal and vertical

Available variants for this product:



AB.0010.1.332
00.00

UI-1550RE-C
CMOS, colour, rolling shutter, 18 fps, High Quality IR-filter

- High Quality IR-filter

- Dimensions: 41x41x40,5mm (HxWxD)

- Weight: 145g

Call for Pricing



Accessories for product "uEye UI-1550RE colour models, UXGA (1600x1200)"

Product image	Item number	Description	Infos
	AD.0040.2.12200 .00	USB 2.0 data cable 5 m – straight, IP65/67 <ul style="list-style-type: none"> ■ shielded USB 2.0 cable ■ straight RE connector to USB-A 	Call for Pricing
	AD.0040.2.12400 .00	USB 2.0 data cable 5 m – 90° angled, IP65/67 <ul style="list-style-type: none"> ■ shielded USB 2.0 cable ■ angled RE connector to USB-A 	Call for Pricing
	AD.0040.2.12600 .00	USB 2.0 trigger/strobe cable 5 m, 90° angled, IP65/67 <ul style="list-style-type: none"> ■ 90° angled RE connector to open ends 	Call for Pricing
	AD.0040.2.13600 .00	USB 2.0 drag chain data cable 8 m – IP65/67, straight <ul style="list-style-type: none"> ■ shielded cable beyond the standards of the USB Implementers Forum Inc. ■ for use in a drag chain or robotic environment ■ straight RE connector to USB-A 	Call for Pricing
	SL.0028.2.06200 .00	uEye RE four Port Hub <ul style="list-style-type: none"> ■ metal case for industrial use. IP 65 / IP67, Clamp for top hat rail mount ■ All connectors can be screwed 	Call for Pricing